

Wirecast Control Surface by X-keys® Specifications

for XK-1506-128WC-R



- Full control of layers, sources and transitions
- Layout designed by Telestream
- For Wirecast Studio or Pro (9 or newer)
- USB connection to computer
- Compatible with both Windows and Mac

A USB controller with dedicated keys for Telestream Wirecast 9 and newer. Includes direct selection of 12 sources on five layers, transition controls and much, much more.

Specifications

Operating System	Windows 7, 8, 10, Mac OS Sierra X, Mac OS X El Capitan
Switch Type	Full-travel rubber dome, carbon on gold contacts, guaranteed for over 1 million operations
Actuation Force	Approx. 2.5 oz (72g) break-over, approx. 1.5 oz (42g) hold
Key Cap Type	UV cured acrylic legends with Cherry MX compatible stem
Key Cap Size	.625" (16mm) sq.
Key Spacing	0.75" O.C.
Optional Keys	2x1, 1x2, and 2x2
Backlighting	128 blue and 128 red LEDs, individually addressable
Connector	Wired USB 3.0 standard "A" plug
Cord Length	118" (3 m)
Dimensions	14" x 7.3" x 1.8" (279mm x 185mm x 46mm)
Weight	4.7 lbs (2.13 kg)
USB type	USB 1.1 compatible through 3.0 Type-c with adapter
Power Source	USB port, nominal voltage = 5 VDC
Current Draw	No backlight: 37 mA, Blue backlight full: 176 mA, Red backlight full: 265 mA, All backlights full: 358 mA
Temperature Range	-20 to 60 C
Memory Capacity	Approximately 21,000 keystrokes or commands in onboard memory
Humidity	80% Rh non-condensing
Environmental Rating	IP 40, typical indoor office environment
Certifications	FCC class B, CE, RoHS, WEEE compliant

Specifications subject to change without notice